



特性カーブ

温度()	抵抗()	公差(%)	公差()
30	439.29	11.50	50.52
35	356.64	11.38	40.59
40	291.46	11.25	32.79
45	239.56	11.11	26.62
50	197.29	11.20	22.10
55	161.46	10.86	17.54
60	134.03	10.04	13.46
65	113.96	9.86	11.23
70	97.05	9.87	9.58
75	82.36	9.49	7.82
80	70.12	9.21	6.46
85	59.73	8.91	5.32
90	51.21	8.48	4.34
95	44.32	8.07	3.58
100	38.47	7.74	2.98
105	33.40	8.18	2.73
110	39.12	8.59	2.50
115	25.53	9.22	2.35
120	22.44	9.89	2.22
125	19.75	10.53	2.08
130	17.44	11.16	1.95

レンジ ; 0 ~ 120

一般仕様
 定格電圧 ; 6V ~ 24V
 測定遅れ ; 電源投入後3分
 使用温度 ; - 25 ~ + 120
 測温素子 ; サミタ
 重 量 ; 40g

WORK . NO.	APPROVED <i>JM</i>	 クリエ電機株式会社 CREATE ELECTRIC CO., LTD SAGAMIHARA JAPAN	TITLE 温度センサ 1線式	
DATE 15.FEB.2008	CHECKED 西川		DWG . NO. 323-801-001-040	REV △
	DESIGNED 阿部			